

ZENNER Stealth Ultrasonic Meters

Models: ZSUS Stainless Steel Housing
ZSU Cast Iron Housing
Sizes 2" through 12"

INTRODUCTION: ZENNER Ultrasonic Meters are designed for applications where high accuracy, long life and a dynamic flow range is desired. The highly advanced, all-digital technology achieves precise measurement without any moving parts, ensuring optimum revenue without compromised performance over time. These meters are used for the measurement of both potable and non-potable clean water in commercial and industrial settings and are capable of bi-directional flow measurement. The meter design has minimal head loss, decreasing pressure complaints from customers and reducing pumping costs for the utility. An industry leading sampling rate of 8 times per second, ensures you are picking up flow changes as they occur making the ZENNER Ultrasonic Meter the most accurate commercial ultrasonic meter in the industry.

OPERATION: ZENNER Ultrasonic Meters use solid state, sound measuring technology to measure instantaneous flow and calculate cumulative flow volume. The LCD display has two rows. The first row shows total volume, where it is factory programmed for US Gallons, Cubic Feet or Cubic Meters. The second row displays additional information such as rate of flow, flow direction, remaining battery life, leak alarms, empty pipe alerts, etc. These meters are capable of ultra precise leak registration with low flow sensitivity as low as .12 GPM.

CONSTRUCTION: ZENNER Ultrasonic Meters consist of three basic components: The main housing, electronics & display package, and four transducers. The ZSU main housing is made of epoxy coated ductile iron. The ZSUS main housing is made of 304 Stainless Steel.

COMMUNICATION: ZENNER Ultrasonic Meters have a universal communication protocol package capable of producing outputs compatible for use with Encoded systems. These meters are designed to be connected to any existing AMR/AMI system.

MAINTENANCE: ZENNER Ultrasonic Meters are engineered and manufactured to provide long-term service and operate virtually maintenance free. There are no moving parts to service. The battery pack has a standard life-time of up to 12 years and is replaceable.

CONFORMANCE: ZENNER Ultrasonic Meters are tested and comply with AWWA Standards C715 and C750. These Meters comply with the lead free provisions of the Safe Drinking Water Act and are certified to NSF/ANSI Standards 61 and 372.

INSTALLATION: ZENNER Ultrasonic Meters are designed to fit the same laying length as most standard turbine meters. With no moving parts to damage, these meters can be used safely and accurately with or without a strainer. These meters are submersible and exceed IP68 standards. These meters can be installed in any position, including horizontal and vertical.



ZSUS03



ZSU03

MODEL		ZSU02 ZSUS02	ZSU03 ZSUS03	ZSU04 ZSUS04	ZSU06 ZSUS06	ZSU08 ZSUS08	ZSU10 ZSUS10	ZSU12 ZSUS12
SIZE		2"	3"	4"	6"	8"	10"	12"
Maximum continuous	USGPM	230	530	910	2,300	2,800	6,000	9,600
High flow rate	USGPM	230	530	910	2,300	2,800	6,000	9,600
Low flow rate	USGPM	.25	.50	.75	2.25	3.5	5.5	9
Start-up flow rate	USGPM	.12	.25	.44	1.12	1.75	2.75	4.50
Maximum working pressure	P.S.I.	225	225	225	225	225	225	225
Pressure loss at the high flow rate	P.S.I.	4.9	1.9	1.9	1.0	1.0		
Operating temperature limits	Deg. F	32 - 122	32 - 122	32 - 122	32 - 122	32 - 122	32 - 122	32 - 122
Length	Inches	10	12	14	18	20	17 3/4	19 11/16
Height	Inches	5 5/8	7 1/2	8 3/4	10 5/8	12 5/8	15 3/16	18 1/8
Width	Inches	6	7 1/2	9	11	13 1/2	16	19
Weight	Pounds	18	36	48	61	94	116	170
Number of holes per flange		2	4	8	8	8	12	12



ZSU02



ZSUS03



ZSU06